

Startgewicht	3000	Bauteile				Schwerpunkt		Abstände				Berechnungen					
		X	Y	Z		X		Y		Z		VA	HA	VL	VR	HL	HR
VA	1600	Bezeichnung	Breite	Tiefe	Höhe	Gewicht	Stirn	v / h	Seite	l / r	Ebene	u / o					
HA	1400																
Radstand	4000					100	600	v					50	50			
Spurweite VA	1800					100	4400	h					50	50			
Spurweite HA	1600					100	2600	v					0	100			
						100	2400	h					0	100			
Aufbau innen:						100	-1400	v					100	0			
Länge	5000					100	6400	h					100	0			
Breite	2400		200			100	600	v					48	53			
Höhe	2000		200			100	4400	h					53	48			
Versatz zur VA	1400		200			100	2600	v					-3	103			
Höhe Fußboden	800		200			100	2400	h					3	98			
			200			100	-1400	v					98	3			
Überhang Heck	2400		200			100	6400	h					103	-3			
Überh. Seitl. VA	300					100	600	v	300	l			50	50	50	0	53
Überh. Seilt. Ha	400					100	4400	h	1200	l			50	50	25	25	25
						100	600	v	2100	l			50	50	0	50	-3
						100	4400	h	2100	r			50	50	50	0	53
Achslast vorn min	28%					100	600	v	1200	r			50	50	25	25	25
Radlast l/r	+/- 4%					100	4400	h	300	r			50	50	0	50	-3
						100	600	v	400	l			50	50	47	3	50
						100	4400	h	1200	l			50	50	25	25	25
						100	600	v	2000	l			50	50	3	47	0
						100	4400	h	2000	r			50	50	47	3	50
						100	600	v	1200	r			50	50	25	25	25
						100	4400	h	400	r			50	50	3	47	0
			200			100	600	v	300	l			50	50	47	3	50
			200			100	4400	h	1200	l			50	50	22	28	22
			200			100	600	v	2100	l			50	50	-3	53	-6
			200			100	4400	h	2100	r			50	50	53	-3	56
			200			100	600	v	1200	r			50	50	28	22	28
			200			100	4400	h	300	r			50	50	3	47	0
			200			100	600	v	400	l			50	50	44	6	47
			200			100	4400	h	1200	l			50	50	22	28	22
			200			100	600	v	2000	l			50	50	0	50	-3
			200			100	4400	h	2000	r			50	50	50	0	53
			200			100	600	v	1200	r			50	50	28	22	28